

SUBMERSIBLE V4

SUBMERSIBLE PUMPSET
50 Hz, 220V & 415V



Farming



Domestic



Gardening



Water Supply



Industrial



BOREWELL SUBMERSIBLE PUMP SETS V4 100 mm (4")

4"



OPI SUBMERSIBLE PUMP V4



4" BOREWELL SUBMERSIBLE PUMPSET -OPI V4



1. DESCRIPTION :

Introducing our 4" Submersible Smart Series : Compact with a 98mm outer diameter, yet powerful, ranging from 0.37 kW to 3.7 kW. Achieve flow rates up to 500 lpm and head heights of 420m.

2. SALIENT FEATURES:

- **Engineered Designs :**
Slim and attractive compact design, with easy installation and maintenance free.
- **High Discharge :**
High operating efficiencies of pumpset result into high water discharge rate and lower power bills.,Guarantees maximum water output for each cycle.
- **No Problems with Suction or Priming :**
Easy to use without requiring constant attention.
- **Impeller & diffuser Bowl :**
High Quality Noryl impeller, a thermoplastic material designed for maximum water flow and efficiency.
- **Water Lubricated Bearings :**
Heavy duty water lubricated journal and Carbon thrust pad with fixed segment bearings for long trouble free operations.
- **Stainless Steel Components :**
All fasteners designed for durability and corrosion resistance..
- **Rigid Construction:**
Built to withstand challenging operational conditions.
- **Low Noise Operation :**
Provides a quiet and disturbance-free environment.
- **Consistent Water Flow :**
Steady and uniform water supply guaranteed.
- **Rotating Parts :**
All rotating components are dynamically balanced to ensure long bearing life and vibration free smooth operation.
- **Wide voltage operation :**
Accommodating fluctuating power supply and safeguarding against electrical inconsistencies.
- **Motor Design :**
The motor is completely designed to avoid sand entry into motor and pump.
- **Attachment :**
Motor and pump is a Couple type, and it is easy for installation.
- **Testing process :** All pumpsets are fully tested and prior to despatch.



OM PRASANTH INDUSTRIES

3. OPERATIONAL CONDITION :

Pump set should be submerged in water with minimum of 0.5m above water level,

- | | | |
|--------------------------------------|-------------------------------------|---|
| • Turbidity : 50 ppm Max | • PH : 6.5 To 8.5 | • Specific Gravity : 1.004 Max |
| • Chlorides : 500 ppm Max | • Temperature : 33 Deg C Max | • Hardness : 300 ppmMax |
| • Total Solids : 3000 ppm Max | • Voltage` : 160 - 420 Volts | • Permissible Amount of sand` : 25 g/ m ³ |

4" BOREWELL SUBMERSIBLE PUMPSET -OPI V4



4. TECHNICAL SPECIFICATION :

SPECIFICATION :

- **Nominal Diameter** : 4"
- **Power Range** : 0.37 kW to 3.7 kW (0.5 HP - 5.0 HP)
- **Supply Type** : Single Phase (50Hz, AC Supply)
Three Phase (50Hz, AC Supply)
- **Voltage Range** : 160 V - 240 V (Single Phase)
350 V - 420 V (Three Phase)
- **Speed** : 2880 RPM
- **Head** : Upto 420 Mtr
- **Flow** : Upto 500 Lpm
- **Liquid / Max Temp** : Clear Water / 33° C ,
- **Type of Duty** : S1 (Continuous)
- **Insulation** : Wet Type, Cat - B, 99.9% Pure Copper
- **Delivery Size** : 1, 1 ½ , 2 , 2 ½ , 3.
- **Max.Outer Diameter** : 96 mm
- **Method of Starting** : 1 PH - Capacitor Start Capacitr Run (CSCR)
3 PH - Direct Online (D.O.L)

5. MATERIAL OF CONSTRUCTION:

- **Impeller & diffuser Bowl** :
High Quality Noryl impller, a thermoplastic material designed for maximum water flow and efficiency.
- **Motor Shaft** :
High Grade stainless steel for durability and anti-rust properties. A sufficient diameter of stainless steel that is ground to precise tolerances and guarantees rigidity.
- **Cable Sealing Arrangement** :
Designed so that no borewell water with sand can enter the motor.
- **Thrust Bearings** :
Carbon Thrust bearing with 4 segment brearing segment and water lubricated to withstand high axial thrust loads.
- **Winding** :
PVC / Polywrap insulated, water cooled.
- **Seal** :
Precision-engineered Mechanical Seal, ensuring leak-proof operation.
- **Casting** :
High Grade cast iron – FG 260.
- **Pressure Equalizing Diaphragm** :
suitably sized to allow for water expansion inside the motor and stop cooling water loss
- **Motor Body and Pump Body** :
SS 202 high graded stainless steel with corrosion resistance
- **Stainless steel components** :
All Fastners, coupling, key stud ring all are high graded stainless steel.



4" BOREWELL SUBMERSIBLE PUMPSET -OPI V4



5.1 MATERIAL OF CONSTRUCTION:

MATERIAL OF CONSTRUCTION			
PUMP MATERIALS		MOTOR MATERIALS	
PART	MATERIAL	PART	MATERIAL
IMPELLER	NORYL	STATOR	LC / CRNO STAMPING
BOWL	NORYL WITH SS RING SS 202	WINDING	POLYWRAP, HIGH GRADED COPPER
DIFFUSERS	SS JACKET	BEARING BUSH	CARBON / LTB 4
SLEEVE BUSH	NITRILE RUBBER	ROTOR	COPPER / ALUMINIUM
SHAFT	SS 410	FASTNERS	SS 304 / SS 202
SLEEVE COUPLING	SS 410	STATOR TUBE	SS 202 / SS 301
PUMP DESIGN	COUPLING TYPE	THRUST PAD ASSMLY	4 SEG / 6 SEG PREMIUM

6. APPLICATIONS :



Residential



Industries



Water Supply



Irrigation



Garden



Sprinkler

7. BENEFITS:

- Residential water needs, daily household requirement.
- Water circulating systems, fountains, lawns and gardens.
- Lifting water from sump to overhead tanks for domestic, individual houses and appartments.
- Irrigation from open wells especially where there is wide fluctuation in water levels.

8. ACCESSORIES AND PACKING ITEM'S :



Cable joining kit



Acrylic Key



Warrenty Card



OM PRASANTH INDUSTRIES

4" BOREWELL SUBMERSIBLE PUMPSET -OPI V4



OM PRASANTH INDUSTRIES